



**REMARK:**  
 1. THE UNIT WEIGHT CAN BE ACCEPTED WITH IN ±3%.  
 2. THE TOLERANCE CAN BE ACCETED AS THE SHEET.

**Specification:**  
 1. Nominal pressure: 1.6MPa;  
 2. Working medium: water;  
 3. Working temperature: -10°C to 120 °C;  
 4. Thread standard: according to ISO228-1;

3	BONNET	BRASS
2	WEDGE	BRASS
1	BODY	BRASS
NO.	PARTS	MATERIAL

CODE NO.	E	A	H	D	L	SW	DN	WEIGHT/G
62510025	1"	63	45	39.5	14	38	22	290
62510032	1-1/4"	72.5	49	47	15.5	47.5	27	490
62510040	1-1/2"	80	52	51.5	15	53.5	31	620
62510050	2"	94	60.5	63.5	16	66	43.5	920
62510065	2-1/2"	102.5	70.5	74	16.5	83.5	53.5	1600
62510080	3"	124	80	89	20	97	62	2400
62510100	4"	160	103	118	26	124	89	4950

**TOLERANCES**

6-30	>30-60	>60-120	>120-200	>200-300
±0.2	±0.3	±0.7	±1	±3

ALL MEASUREMENTS IN MM

DESIGNED & PRODUCED BY: **BRASS SWING CHECK VALVE**

**DAWOO VALVE**

DAWOO VALVE CO., LTD.  
 大禹阀门有限公司  
 25MM-100MM

CONTROLLED DOCUMENTS  
 受控文件

DRAWING NO.: SLZHF62510025-100 (2015)  
 DATED: DEC. 7TH, 2015